

===== SECTION VI - HEALTH HAZARD DATA =====**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

INHALATION: Headache, Nausea, Respiratory Irritation.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

EYE CONTACT: Causes severe eye irritation.

SKIN CONTACT: Prolonged contact may cause defatting and irritation of the skin.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SKIN ABSORPTION: No evidence of harmful effects from available information.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INGESTION: Harmful if swallowed.

HEALTH HAZARDS (ACUTE AND CHRONIC): See above for acute health hazards.

CHRONIC-None known.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No No.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Those of the respiratory system and skin.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove victim to fresh air immediately. If coughing, difficult breathing or any other respiratory symptoms persist, seek medical attention at once.

EYE CONTACT: Immediately flush with running water for at least 15 minutes, lifting eyelids periodically to remove contamination. Get medical attention if irritation persists.

SKIN CONTACT: Wash thoroughly with soap and water and see a doctor if irritation persists.

INGESTION: If swallowed immediately give 1 or 2 glasses of water followed by citrus juice if available. Call a physician, hospital emergency room or poison control center.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Keep spectators away.

Eliminate all ignition sources (flames, hot surfaces and sources of electrical, static or frictional sparks) and ventilate area. Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered metal containers for recovery or disposal or remove with inert absorbent. Use only non-sparking tools. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams and groundwater with spilled material or used absorbent.

WASTE DISPOSAL METHOD: Dispose in accordance with federal, state and local regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Wash thoroughly after handling. Do not store above 115 degrees F (46 degrees C) store large quantities in compliance with OSHA 29 CFR 1910.106.

OTHER PRECAUTIONS: Close container after each use. Do not weld, braze or cut an empty container. Empty container must not be washed and reused for any purpose. Use only with adequate ventilation or with proper respiratory protection. Keep out of Reach of Children.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION: Not required under normal conditions of use.

VENTILATION: General mechanical ventilation or local exhaust.

PROTECTIVE GLOVES: Not required.

EYE PROTECTION: Not required under normal use conditions.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: NOT APPLICABLE

WORK/HYGIENIC PRACTICES: Avoid breathing spray mist.

===== SECTION IX - DISCLAIMER =====

The information contained herein is based on data considered to be accurate. While the information is believed to be reliable, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. It is the user's obligation to evaluate this information and determine the conditions of the safe use of the product.